

Single-Phase

Type No.	Max. Power (KW)	current (A)	pressure/ vacuum (mmAq)	Max. airflow (m3/min)	Noise value(dB)	Drawing caliber(Inch)	Approx. weight(Kg)
50Hz IP54 100-110/200~220V							
LG-2068A	0.4	4.0/2.0	1100/1000	1.33	61	1-1/4	12
LG-3068A	0.8	10.5/4.8	1900/1400	2.4	68	1-1/2	17
LG-5068A	1.75	10	2800/2300	4.2	75	2	27
600Hz IP54 100-110/200~220V							
LG-2068A	0.4	5.8/2.8	1700/1500	1.55	63	1-1/4	12
LG-3068A	0.8	12.0/6.0	2400/2100	2.65	69	1-1/2	17
LG-5068A	1.75	10.0	3700/3250	4.6	78	2	27

Three-Phase

Type No.	Max. Power (KW)	current (A)	pressure/ vacuum (mmAq)	Max. airflow (m3/min)	Noise value(dB)	Drawing caliber(Inch)	Approx. weight(Kg)
50Hz IP54 200-220V/380-415V							
LG-2068	0.4	1.6/0.9	1100/1000	1.2	61	1-1/4	12
LG-3068	0.8	3.5/1.9	2000/1500	2.19	68	1-1/2	17
LG-5068	1.75	5.8/3.5	2900/2400	2.2	71	1-1/2	19.5
LG-6068	2.2	12/6.9	3400/2500	4.59	75	2	38
LG-7068	3.7	13/7.5	3400/2500	4.59	75	2	38
LG-8068	5.5	20/11.5	3500/2750	8.76	76	2-1/2	78
60Hz IP54 200-220V/380-415V							
LG-2068	0.5	2.2/1.25	1500/1300	1.21	66	1-1/4	12
LG-3068	0.9	4.2/2.2	2800/2100	2.64	70	1-1/2	17
LG-5068	1.9	7/4.0	4000/2800	3.9	78	2	27
LG-6068	2.6	10/5.8	4300/3000	5.73	80	1-1/2	19.5
LG-7068	4	14/8.0	4300/3000	5.73	80	2	27
LG-8068	6	25/15	4750/3550	10.37	86	1-1/2	19.5

- Please indicate the voltage and frequency of the blower when placing an order.